

TECHNICAL SHEET

**DFX SERIES
DIAMOND FLOW CARTRIDGES**



TECHNICAL SHEET



PENTAIR DFX SERIES DIAMOND FLOW CARTRIDGES

TECHNICAL CHARACTERISTICS

- Temperature rating: 4.4 °C - 51.6°C
- Exterior filter media: Polypropylene polyspun
- Interior filter media: Carbon block
- End caps: Polypropylene
- Gaskets: Buna-N



PERFORMANCE CHARACTERISTICS

Model	Initial ΔP @ flow rate	Chlorine taste & Odor reduction @ Flow rate
DFX-CB-10	0.07 bar @ 3.8 Lpm	9'460 L @ 3.8 Lpm
DFX-CB-20	0.07 bar @ 7.6 Lpm	18,927 L @ 7.6 Lpm
DFX-CB-BB	0.07 bar @ 7.6 Lpm	56,781 L @ 7.6 Lpm

PRODUCT SPECIFICATIONS

Model	Maximum dimensions	Micron rating (nominal)
DFX-CB-10	73.41 mm x 249.934 mm (2.89" x 9.84")	10
DFX-CB-20	73.41 mm x 509.651 mm (2.89" x 20.065")	10
DFX-CB-BB	117.60 mm x 249.935 mm (4.63" x 9.840")	10